

23-44
Watt



SELV

 AC/DC

PF
 $\lambda \geq 0,95$

IP20

CE

EMC





M

M

F



 37 mm

$t_a -10^{\circ}\div +40^{\circ}\text{C}$

 25 ^{®Pending}

DALI
Dimmable


Dimmable



Part Number	Iout	Vout Led Min	Vout Led Max	W	Dimensions A x B x C	Protocol
A40CC23WD00B	100÷700mA	2,5V	2,5-46VDC	23W	163 x 30 x 21	DALI / PUSH
A40CC36WD00B	150÷900mA	2,5V	2,5-50VDC	36W	163 x 30 x 21	DALI / PUSH
A40CC44WD00B	300÷1050mA	9V	2,5-49V	44W	163 x 30 x 21	DALI / PUSH

 Alimentatore Multicurrent per LED

- Alimentatore indipendente - IP40 - Classe II di isolamento - SELV
- Memoria di regolazione anche in assenza di rete
- Uscita in corrente costante regolabile tramite DIP-Switches da 100 a1050mA, $\pm 5\%$
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Morsetti rapidi
- Alto fattore di potenza
- Spessore ridotto
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 200V $\div$ 240V/AC - Uscita stabilizzata

 Multicurrent LED Driver Multicurrent

- For independent mounting - IP40 - Insulation class II - SELV
- Memory of regulation even with mains not connected
- Output in constant current from100 to 1050mA $\pm 5\%$ settable by Dip-Switches
- Self-resetting protection against overtemperatures, open circuit and against output short circuits
- Fast terminals
- High power factor
- Reduced thickness
- Cable clamp for flat and round cables
- Input voltage: 200V $\div$ 240V/AC - Steady output

