



Part Number	Output V	Output I _{max}	W	Dimensions A x B x C	Protocol
A40PBT10000B	24V/DC	4,16A	100W	210 x 75 x 35	TRIAC / IGBT / MOSFET
A40PBT15000B	24V/DC	6,25A	150W	210 x 75 x 35	TRIAC / IGBT / MOSFET
A40PBT20000B	24V/DC	8,33A	200W	210 x 75 x 35	TRIAC / IGBT / MOSFET

🇮🇹 Alimentatore dimmerabile per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Regolazione della luce con dimmer TRIAC/IGBT/MOSFET sul lato primario con minimo regolabile, compatibili con carichi LED
- Uscita in tensione costante 24V, +/-5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Morsetti rapidi
- Doppio morsetto di uscita
- Alto fattore di potenza
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 230V/AC +/- 10% - Uscita stabilizzata.

🇬🇧 Dimmable driver for High Brightness LEDs

- For independenty use - IP20 - Insulation class II
- Light regulation by primary side TRIAC/IGBT/MOSFET dimmer with settable minimum, compatible with LED loads.
- Output in steady voltage 24V, +/-5%
- Self-resetting protection against overtemperatures against open circuit and against output short circuits.
- Fast terminals
- Double output
- High power factor
- Cable clamp for flat and round cables
- Input voltage: 230V/AC +/- 10% - Steady output.