




t 25 18/ap verticale  
E14 max 40w - 230V





<i>totalwhite</i>	ap00832	•
<i>totalblack</i>	ap00833	•
ottone grezzo - bianco/raw brass - white	ap00834	•
ottone grezzo - nero/raw brass - black	ap00835	•




t 25 45/ap orizzontale  
E14 max 40w - 230V

<i>totalwhite</i>	ap00828	•
<i>totalblack</i>	ap00829	•
ottone grezzo - bianco/raw brass - white	ap00830	•
ottone grezzo - nero/raw brass - black	ap00831	•






† 25 35/so  
E14 max 40w - 230V




<i>totalwhite</i>	so01448	•
<i>totalblack</i>	so01449	•
<i>ottone grezzo - bianco - cavo bianco</i> <i>raw brass - white - white cable</i>	so01450	•
<i>ottone grezzo - nero - cavo nero</i> <i>raw brass - black - black cable</i>	so01451	•

† 25 70/so  
E14 max 40w - 230V




<i>totalwhite</i>	so01289	•
<i>totalblack</i>	so01290	•
<i>ottone grezzo - bianco - cavo bianco</i> <i>raw brass - white - white cable</i>	so01291	•
<i>ottone grezzo - nero - cavo nero</i> <i>raw brass - black - black cable</i>	so01292	•

† 25 140/so  
E14 max 40w - 230V




<i>totalwhite</i>	so01297	•
<i>totalblack</i>	so01298	•
<i>ottone grezzo - bianco - cavo bianco</i> <i>raw brass - white - white cable</i>	so01299	•
<i>ottone grezzo - nero - cavo nero</i> <i>raw brass-black - black cable</i>	so01300	•

317

dimmerabile utilizzando una lampada dim  
dim luminaire using dimmable lamp 


fornite con lampada tubolare sabbiata led cod. lamled085 - 5w 440lm 3000K  
supplied with tubular led frosted lamp code lamled085 - 5w 440lm 3000K

a richiesta lampada tubolare chiara led cod. lamled096 - 5w 480lm 3000K  
supplied on demand with tubular clear lamp led code lamled096 - 5w 480lm 3000K




318

**t.ball 35/pl dim 0-10**  
 7,5w 700mA 810lm 3000K - 230V  
 fornito con driver e modulo led  
 luminaire contains driver and led




<i>totalwhite</i> - bianco-latte/opal	pl01833
<i>totalblack</i> - trasparente/clear	pl01834
ottone grezzo - nero - trasparente	pl01836
raw brass - black - clear	

**t.ball 70/pl dim 0-10**  
 7,5w 700mA 810lm 3000K - 230V  
 fornito con driver e modulo led  
 luminaire contains driver and led



<i>totalwhite</i> - bianco-latte/opal	pl01838
<i>totalblack</i> - trasparente/clear	pl01839
ottone grezzo - nero - trasparente	pl01841
raw brass - black - clear	

**t.ball 100/pl dim 0-10**  
 7,5w 700mA 810lm 3000K - 230V  
 fornito con driver e modulo led  
 luminaire contains driver and led




<i>totalwhite</i> - bianco-latte/opal	pl01828
<i>totalblack</i> - trasparente/clear	pl01829
ottone grezzo - nero - trasparente	pl01831
raw brass - black - clear	

a richiesta 2700/4000K  
 2700/4000K on demand





**t-five 125/so**  
G5 18w 72V 2700K 1440lm 140° - 230V



<i>totalwhite</i>	so00946	•
<i>totalblack</i>	so00947	•
brunito verniciato - cavo nero/old brass painted - black cable	so00948	•
verniciato ottone - cavo nero/painted brass - black cable	so01009	•

fornita con lampada tubolare opale led G5 cod. lamled062 18w 1440lm 2700K  
supplied with tubular opal led lamp G5 code lamled062 18w 1440lm 2700K




**t-five 125/so dim 0-10 plus**  
23w 24V 3300lm 3000K - 230V  
fornito con driver e modulo led-strip  
luminaire contains driver  
and led-strip



<i>totalwhite</i>	so03612
<i>totalblack</i>	so03613
brunito verniciato - cavo nero/old brass painted - black cable	so03614
verniciato ottone - cavo nero/painted brass - black cable	so03615
color - azzurro, rosso - cavo arancio	so03658
color - light blue, red - orange cable	

a richiesta 2700/4000K  
2700/4000K on demand

**89/1180mm accessorio schermo**



lamiera in acciaio verniciato <i>totalwhite</i> iron light protection <i>totalwhite</i> painted	acc00387
lamiera in acciaio verniciato <i>totalblack</i> iron light protection <i>totalblack</i> painted	acc00388
lamiera in acciaio verniciato giallo iron light protection yellow painted	acc00671
lamiera in acciaio brunito verniciato iron light protection old brass painted	acc00483 1